



Jetway IPC

Top Quality • Stable & Solid

2018/2019 All-In-One Brochure





Model	HA270SAG-H110-S	HA270SAG-H110-W
Body color	Silver	White
Viewable Size Image	27.0" With LED Backlight	27.0" With LED Backlight
Active Area	527.04(H) x296.46(V)	527.04(H) x296.46(V)
Touch Support	No	No
Resolution	1920 x1080 @ 60Hz	1920 x1080 @ 60Hz
Display Color	16.7M	16.7M
Pixel Pitch	0.3112 x 0.3112mm	0.3112 x 0.3112mm
Aspect Ratio	16:9	16:9
Contrast Ratio	3000:1	3000:1
Viewing Angle(H/V)	H178/V178	H178/V178
Response Time	12 ms	12 ms
Form Factor	Thin Mini ITX	Thin Mini ITX
Processor	INTEL® LGA1151 series Processor	INTEL® LGA1151 series Processor
System Chipset	INTEL® H110 Express Chipset	INTEL® H110 Express Chipset
System Memory	DDR4 2133 Memory, Max 32GB	DDR4 2133 Memory, Max 32GB
BIOS	128MB SPI Flash ROM	128MB SPI Flash ROM
Ethernet	1* 10/100/1000Mbps LAN	1* 10/100/1000Mbps LAN
Audio	Realtek® ALC662 HD Audio	Realtek® ALC662 HD Audio
Storage	1* 2.5" SATA HDD 1* M-SATA connector	1* 2.5" SATA HDD 1* M-SATA connector
WIFI Module	PCI-E mini card for WLAN	PCI-E mini card for WLAN
TPM	Supports TPM optional	Supports TPM optional
Expansion	HDMI+DP	HDMI+DP
Display Output	4* USB3.0, 2* USB2.0,1* HDIM, 1 * DP	4* USB3.0, 2* USB2.0,1* HDIM, 1 * DP
I/O Port	1* LAN, 1* Line-out, 1* MIC,1* DC Jack	1* LAN, 1* Line-out, 1* MIC,1* DC Jack
Power Adapter	DC-IN 19V-120W	DC-IN 19V-120W
OS Support	Windows 7/8.1/10	Windows 7/8.1/10
Temperature Range	Operating: 0°C ~ 50°C	Operating: 0°C ~ 50°C
Humidity	20%~90% (non condensing)	20%~90% (non condensing)
Certification	CE, FCC, LVD,ROHS	CE, FCC, LVD,ROHS



HA238SA-H110	HA238SAH-H110-S	HA238SAH-H110-W
Silver	Silver	White
23.8 inch With LED Backlight	23.8 inch With LED Backlight	23.8 inch With LED Backlight
527.04(H) x296.46(V)	527.04(H) x296.46(V)	527.04(H) x296.46(V)
No	Yes (PCAP Multi point touch)	Yes (PCAP Multi point touch)
1920 x 1080 @60Hz	1920 x 1080 @60Hz	1920 x 1080 @60Hz
16.7M	16.7M	16.7M
0.274 x 0.274 mm	0.274 x 0.274 mm	0.274 x 0.274 mm
16:9	16:09	16:09
3000:1	3000:1	3000:1
H178/V178	H178/V178	H178/V178
24ms	24ms	24ms
Thin Mini ITX	Thin Mini ITX	Thin Mini ITX
INTEL® LGA1151 series Processor	INTEL® LGA1151 series Processor	INTEL® LGA1151 series Processor
INTEL® H110 Express Chipset	INTEL® H110 Express Chipset	INTEL® H110 Express Chipset
DDR4 2133 Memory, Max 32GB	DDR4 2133 Memory, Max 32GB	DDR4 2133 Memory, Max 32GB
128MB SPI Flash ROM	128MB SPI Flash ROM	128MB SPI Flash ROM
1* 10/100/1000Mbps LAN	1* 10/100/1000Mbps LAN	1* 10/100/1000Mbps LAN
Realtek® ALC662 HD Audio	Realtek® ALC662 HD Audio	Realtek® ALC662 HD Audio
1* 2.5" SATA HDD	1* 2.5" SATA HDD	1* 2.5" SATA HDD
1* M-SATA connector	1* M-SATA connector	1* M-SATA connector
PCI-E mini card for WLAN	PCI-E mini card for WLAN	PCI-E mini card for WLAN
Supports TPM optional	Supports TPM optional	Supports TPM optional
HDMI+DP	HDMI+DP	HDMI+DP
4* USB3.0, 2* USB2.0,1* HDIM, 1 * DP	4* USB3.0, 2* USB2.0,1* HDIM, 1 * DP	4* USB3.0, 2* USB2.0,1* HDIM, 1 * DP
1* LAN, 1* Line-out, 1* MIC,	1* LAN, 1* Line-out, 1* MIC,	1* LAN, 1* Line-out, 1* MIC,
1* DC Jack	1* DC Jack	1* DC Jack
DC-IN 19V-120W	DC-IN 19V-120W	DC-IN 19V-120W
Windows 8.1/10	Windows 8.1/10	Windows 8.1/10
0~ +50°C (Operating)	0~ 50°C (Operating)	0~ 50°C (Operating)
20%~90% (non condensing)	20%~90% (non condensing)	20%~90% (non condensing)
FCC, CE, RoHS	FCC, CE, RoHS	FCC, CE, RoHS



- TW Add: 9F., NO.207, Sec. 3, Beixin Rd., Xindian Dist., New Taipet City 23143, Taiwan (R.O.C)
Tel : +886-2-89132711 Fax : +886-2-89132722
- CN Add (Dongguan) : No. 605, 8th Commercial Office Building, Vanke Center, Changqing South Road, Changan, Dongguan City, 523850, China
Tel : +86-769-2101-8010 Mobile : +86-138-2880-2876
- Factory (Fujian) Add : FUJIAN CANDID ENTERPRISE CO.,LTD., North Industrial Park, Changshan Economic Development Zone, Yunxiao County, Zhangzhou, Fujian Provice 363307, China.
Tel : +86-596-8625168

All brand names and products are registered trademarks of their respective companies.



Z-A94-F