

# Index

- Ablation 105, 195, 554, 558, 559, 572, 575
- Acceleration 42, 48, 49, 59, 139, 351, 550, 592
- Acoustic balance 177, 186
- Acoustic modes 65, 173-175
- Adhesion 554-558, 574, 576
- Afterburning 199, 341, 400, 402, 511, 513, 561
- Aging 364, 365, 370, 408, 409, 432, 465, 517-519, 554, 561, 562
- Airbreathing motors 26, 106-109, 594, 595
- Aluminum 5, 11, 42-46, 96, 126, 139, 357, 403, 438, 462, 488, 497, 498, 533, 551
- Ammonium nitrate 416, 429, 437, 463, 466, 599
- Ammonium perchlorate 42-46, 96, 125, 127, 197, 316, 341, 348, 357, 416, 428, 435, 460, 461, 462, 487, 490, 496, 498, 504, 509, 510, 517, 520, 534
- Anisotropy 451-454
- Antioxidant 432
- Azide 483, 587, 588
- Ballistic modifier 123, 128, 372, 376, 396, 408, 427-428, 488, 513
- Base bleed 349
- Beryllium 438, 586
- Binder 42, 46, 126, 130, 237, 415, 416, 417, 418, 430, 433, 440, 471, 479, 480, 505, 516, 530, 571, 576, 585
- Blast tube 8
- Bond 265-269, 454
- Bonding 185, 215, 294, 417, 455, 494, 549, 554, 556, 562, 563, 564, 565, 567, 580
- Bonding agent 430, 486, 555
- Boron 357, 438, 533, 534, 537, 545, 549, 590
- Burning area 55-57, 75, 100
- Burning rate 10, 12, 13, 58, 61, 63, 82, 100, 111-117, 307, 334, 335, 351, 356, 375, 394, 395, 468, 488, 489, 506, 508
- Burning rate accelerator 427
- Burning rate enhancement 83, 136, 561, 562
- Burning rate law 14, 59, 112, 128
- Burning rate models 124, 129, 132
- Burning rate moderator 428
- Carbon-carbon 8
- Card gap test 309, 312, 322, 412, 520, 521
- Case 2-5, 50, 343, 344, 454, 472, 494, 549, 567, 568, 570, 592
- Case bonded grain 5, 37, 79, 218, 280, 338, 343, 415, 417, 448, 453, 455, 478, 493, 500, 503, 549, 566, 567, 576
- Casting 37, 383, 388, 416, 442-450, 453, 497, 502, 566
- Casting powder 42, 371, 377, 383, 385, 387, 478, 490, 491, 492, 502, 520, 521
- Casting solvent 383, 386, 387, 480, 502
- Catalyst 431, 442, 486, 571
- Centrifugation 568
- Char 554, 558, 574
- Chemical stability 371, 404-408, 497, 515
- Clean propellant 600
- Combustion instability 64, 80, 81, 172, 373, 401-404, 513-515
- Combustion mechanism 121, 124, 131
- Combustion efficiency 26, 530, 537, 544, 548
- Compatibility 376, 416, 434, 483, 554, 556, 562, 563, 586
- Condensed phase 24, 85, 142
- Conductive combustion 305, 307
- Coning 41, 83
- Continuous mixing 442, 596, 599
- Convective combustion 305, 306, 308
- Cook-off 218, 306, 317, 318, 347, 348, 411, 467, 471, 497
- Cost 4, 42, 81, 343-345, 351, 361, 551, 553, 596, 598, 600, 601
- Creep 243, 246
- Crosslinking 416, 418, 423, 425, 464, 466, 480, 492, 496, 504, 505, 568, 574, 576
- Crystallization 487, 499-500
- Curing 4, 5, 220, 383, 388, 416, 431, 450, 464, 485, 496, 497, 506, 518, 522, 576, 599

- Damage 261, 288, 294, 453
- Damping 179, 188, 376, 403, 514
- Deflagration 305, 520
- Deflagration to detonation transition 309-311, 323, 520, 522, 589
- Density 8, 10, 21, 332, 385, 386, 387, 391, 436, 490, 493, 497, 510, 531, 532, 533, 554, 572, 580, 594
- Design to cost 362
- Detonation 304, 306, 308, 314, 316, 346, 347, 411, 467, 469, 521
- Detonation critical diameter 49, 308, 325, 347, 348, 412, 469
- Discharge coefficient 10, 11, 20, 89
- Dynamic loads 297-300
- End burning grains 40, 41, 83, 97, 383, 390, 548, 559
- Equivalence ratio 534, 539, 545, 548
- Erosive burning 52, 61-63, 75, 157-164, 404
- Expansion ratio 7, 23, 55, 75, 89
- Extrusion 42, 379, 383, 384
- Failure criteria 71, 77, 257-261
- Ferrocenic derivative 128, 427, 461, 468-471
- Finocyl 40, 137, 156, 175, 453
- Flash suppressor 210, 376, 400, 408, 513
- Flow 15, 24, 31, 59, 86, 140, 153-157, 194
- Flow rate 10, 11, 89, 335, 356, 534, 539, 544
- Fluoramine compounds 587, 588
- FMECA 76
- Free standing grain 5, 37, 40, 222, 343, 500, 566, 575
- Friction sensitivity 314, 315, 411, 470, 521, 522, 543
- Fuel rich propellants 106, 527, 529, 532, 535, 538-545, 548
- GAP 587
- Gas generator 2, 106, 158, 350, 351-354, 460, 463, 528, 539, 545, 548, 590
- Glass transition temperature 336, 421, 497, 498
- Hazard division 320-324, 345, 522
- Heat capacity 391
- Heat of combustion 530, 532
- Heat of explosion 386, 391, 398, 403, 407
- Heat transfer 15, 159, 160, 168, 354
- HMX 42-46, 125, 344, 437, 462, 487, 507, 586, 590
- Hump effect 59, 136, 137, 451, 452
- Igniter 354, 355, 356
- Ignition 3, 4, 9, 42, 51, 63, 67, 75, 80, 167-172, 304, 314, 316, 317, 338, 351, 354, 356, 372, 379, 410, 469, 473, 537
- Ignition delay 169
- Ignition compositions 356-359
- Impact sensitivity 313, 411, 543
- Incompressible 67, 68, 250, 282-286
- Infrared 201, 203, 208, 399
- Inhibitor 380, 381, 553, 566, 570, 571, 590
- Insensitive munitions 4, 345-347
- Integral booster 81, 526, 549, 579
- Integral molding 450, 486, 497
- Isocyanate 423, 485, 492, 496, 571, 574, 576
- Klemmung (burning area to throat area ratio) 11, 13, 14, 75, 93, 185, 323
- Kneading 377, 378, 384
- L\* instabilities 173, 177
- Labor regulations 320, 322
- Liner 6, 38, 417, 454, 494, 550, 553, 567, 576, 578
- Longitudinal instabilities 173, 181, 401
- Loss 24, 25, 97, 180
- Mandrel 3, 4, 38, 443, 446, 449, 452, 567
- Mass flow rate 1, 17, 19, 27, 48, 63, 75, 130
- Mass flow rate response 175, 176
- Mechanical behavior 66, 67, 227, 235, 239, 251, 274, 298, 336, 393, 502, 505, 522
- Mechanical capability 66, 71, 77, 217, 268, 339, 341, 463, 464
- Mechanical imbedment 569
- Mechanical loads 35, 68, 70, 77, 218, 338, 416
- Migration 427, 454, 466, 518, 562
- Mixer 384, 441, 496, 599
- Mixing 383, 384, 416, 439-442, 496, 568, 600
- Molding 450
- Monolithic boosters 600
- Nitramine 125, 483, 487, 490, 496, 498, 510, 517, 520, 562
- Nitrocellulose 42, 329, 370, 373, 377, 383, 384, 477, 481, 504
- Nitroglycerine 42, 329, 370, 374, 377, 383, 384, 386, 477, 483, 496, 499, 500, 587
- Nitroguanidine 374, 429, 437, 461
- Nondestructive inspection 364, 454-461, 565, 599, 600
- Nozzle 6-9, 15, 16, 17, 18, 27, 50, 51, 59, 75, 89, 92-94, 107, 180, 194, 344, 525, 526, 547, 549, 590
- Nozzleless motors 81-82, 549, 550, 595
- Operating pressure 7, 12, 22, 75, 102, 402
- Optical transmission 95, 201, 206, 399, 559-561
- Overtest 78
- Oxamide 429, 575
- Paste 378
- Peeling 270, 563, 570
- Plasticizer 371, 375, 422, 425, 427, 479, 480, 481, 483, 495, 498, 499, 562, 571, 578
- Plateau 372, 395, 396, 397, 507-508
- Plume 48, 97, 193, 199, 204, 560
- Poisson ratio 227, 229, 230, 283
- Polybutadiene 45, 96, 417, 423, 427, 432, 461-462, 471, 474, 530, 534, 540, 576, 585, 598, 599
- Polyester 421, 432, 462, 474, 481, 504, 510, 530, 571, 574
- Polyether 421, 460, 481, 510, 574
- Post boost control system 462, 589
- Pot life 416, 431, 542, 566, 567, 599
- Preliminary design 3, 20, 21, 36, 52, 72-75
- Pressure coupling 175, 178, 181
- Pressure effect 249, 252-261
- Pressure exponent 58, 112, 128, 396, 427, 463, 489, 510, 547, 550
- Pressurization 70, 220, 223, 224
- Primary smoke 196, 211, 341, 512
- Pyrolysis 41, 118, 554, 558, 561, 574
- Pyrotechnic behavior 304, 467, 595
- Radar attenuation 200, 206, 210
- Ramjet 26-31, 106-109, 335, 351, 525, 526, 528, 535, 549, 579, 595, 601
- Ramrocket 26-31, 335, 351, 539, 595, 601
- RDX 42-46, 125, 487, 504, 507
- Relaxation 67, 243, 244
- Reliability 35, 37, 49, 75-78, 218, 362, 574, 592, 598, 600
- Resonance rod 187
- Reynolds number 161
- Rolling 379, 383
- Safety 49, 303, 345, 358, 410-412, 442, 449, 467, 495, 519-523, 543
- Safety coefficient, safety factor .65, 70, 71, 72, 74-77, 216, 288-297, 519
- Safety margin 65, 77, 217
- Screw extrusion 343, 377, 382, 390, 596
- Secondary smoke 197, 212, 341, 512
- Segmented grain 79, 80, 598
- Service life 35, 40, 360, 363, 405, 406, 553, 571, 589, 592
- Shear 233, 443, 454
- Shell 349, 597
- Shock sensitivity 386, 470, 521, 522
- Signature 193, 194, 333, 341, 342, 399, 460, 511, 515, 530, 544, 549, 561, 572, 591
- Space motors 79, 80, 597-600
- Specific impulse 19, 21, 25, 27, 81, 85, 96-106, 332-333, 398, 426, 434, 460, 493, 510-512, 534, 538, 542, 545, 549, 586, 588, 589, 594, 595, 597
- Spraying 566, 568
- Stabilizer 317, 371, 375, 376, 405, 408, 488, 516
- Stamping 343, 381, 448
- Standard motor 11, 99, 116
- Standard specific impulse 10, 54, 105, 106, 108
- Static electricity 319, 411, 471-473, 523, 578
- Steady state combustion 10, 93, 135
- Steady state flow 91, 92
- Strain 67, 70, 128, 217, 225-229, 237, 270, 276, 291, 417, 501, 502, 503, 592
- Strand burner 113, 307
- Stress 67, 70, 138, 217, 225-229, 237, 270, 276, 293, 417, 466, 501, 502, 503, 592
- Structural analysis 36, 52, 53, 65, 74, 215
- Structural integrity 52, 82, 216
- Swelling 377, 380, 419, 571
- T burner 181, 182
- Tear 262
- Temperature coefficient 14, 59, 112, 335, 372, 375, 395, 507, 539
- Tensile test 71, 233-236, 240-242, 501
- Terminology 47-48
- Theoretical specific impulse 24, 96
- Thermal conductivity 391, 554, 580
- Thermal cycles 42, 48, 49, 295, 338-340, 501, 592, 601
- Thermal expansion coefficient 340, 391, 417, 499, 580
- Thermal explosion 307, 317
- Thermal insulation 5, 6, 50, 454, 553, 554, 567, 590
- Thermal protection 3, 44, 494, 549, 550, 558, 579
- Thermal shrinkage 280
- Thermoinitiation 317, 410, 470, 523
- Thrust 1, 15, 17, 19, 30, 48, 52, 53, 79, 80, 416, 598
- Thrust coefficient 18, 31, 89
- Thrust law 13
- Thrust measurement 97, 98

- Nozzle 6-9, 15, 16, 17, 18, 27, 50, 51, 59, 75, 89, 92-94, 107, 180, 194, 344, 525, 526, 547, 549, 590
- Nozzleless motors 81-82, 549, 550, 595
- Operating pressure 7, 12, 22, 75, 102, 402
- Optical transmission 95, 201, 206, 399, 559-561
- Overtest 78
- Oxamide 429, 575
- Peeling 270, 563, 570
- Plasticizer 371, 375, 422, 425, 427, 479, 480, 481, 483, 495, 498, 499, 562, 571, 578
- Plateau 372, 395, 396, 397, 507-508
- Plume 48, 97, 193, 199, 204, 560
- Poisson ratio 227, 229, 230, 283
- Polybutadiene 45, 96, 417, 423, 427, 432, 461-462, 471, 474, 530, 534, 540, 576, 585, 598, 599
- Polyester 421, 432, 462, 474, 481, 504, 510, 530, 571, 574
- Polyether 421, 460, 481, 510, 574
- Post boost control system 462, 589
- Pot life 416, 431, 542, 566, 567, 599
- Preliminary design 3, 20, 21, 36, 52, 72-75
- Pressure coupling 175, 178, 181
- Pressure effect 249, 252-261
- Pressure exponent 58, 112, 128, 396, 427, 463, 489, 510, 547, 550
- Pressurization 70, 220, 223, 224
- Primary smoke 196, 211, 341, 512
- Pyrolysis 41, 118, 554, 558, 561, 574
- Pyrotechnic behavior 304, 467, 595
- Radar attenuation 200, 206, 210
- Ramjet 26-31, 106-109, 335, 351, 525, 526, 528, 535, 549, 579, 595, 601
- Ramrocket 26-31, 335, 351, 539, 595, 601
- RDX 42-46, 125, 487, 504, 507
- Relaxation 67, 243, 244
- Reliability 35, 37, 49, 75-78, 218, 362, 574, 592, 598, 600
- Resonance rod 187
- Reynolds number 161
- Rolling 379, 383
- Safety 49, 303, 345, 358, 410-412, 442, 449, 467, 495, 519-523, 543
- Safety coefficient, safety factor .65, 70, 71, 72, 74-77, 216, 288-297, 519
- Safety margin 65, 77, 217
- Screw extrusion 343, 377, 382, 390, 596
- Secondary smoke 197, 212, 341, 512
- Segmented grain 79, 80, 598
- Service life 35, 40, 360, 363, 405, 406, 553, 571, 589, 592
- Shear 233, 443, 454
- Shell 349, 597
- Shock sensitivity 386, 470, 521, 522
- Signature 193, 194, 333, 341, 342, 399, 460, 511, 515, 530, 544, 549, 561, 572, 591
- Space motors 79, 80, 597-600
- Specific impulse 19, 21, 25, 27, 81, 85, 96-106, 332-333, 398, 426, 434, 460, 493, 510-512, 534, 538, 542, 545, 549, 586, 588, 589, 594, 595, 597
- Spraying 566, 568
- Stabilizer 317, 371, 375, 376, 405, 408, 488, 516
- Stamping 343, 381, 448
- Standard motor 11, 99, 116
- Standard specific impulse 10, 54, 105, 106, 108
- Static electricity 319, 411, 471-473, 523, 578
- Steady state combustion 10, 93, 135
- Steady state flow 91, 92
- Strain 67, 70, 128, 217, 225-229, 237, 270, 276, 291, 417, 501, 502, 503, 592
- Strand burner 113, 307
- Stress 67, 70, 138, 217, 225-229, 237, 270, 276, 293, 417, 466, 501, 502, 503, 592
- Structural analysis 36, 52, 53, 65, 74, 215
- Structural integrity 52, 82, 216
- Swelling 377, 380, 419, 571
- T burner 181, 182
- Tear 262
- Temperature coefficient 14, 59, 112, 335, 372, 375, 395, 507, 539
- Tensile test 71, 233-236, 240-242, 501
- Terminology 47-48
- Theoretical specific impulse 24, 96
- Thermal conductivity 391, 554, 580
- Thermal cycles 42, 48, 49, 295, 338-340, 501, 592, 601
- Thermal expansion coefficient 340, 391, 417, 499, 580
- Thermal explosion 307, 317
- Thermal insulation 5, 6, 50, 454, 553, 554, 567, 590
- Thermal protection 3, 44, 494, 549, 550, 558, 579
- Thermal shrinkage 280
- Thermoinitiation 317, 410, 470, 523
- Thrust 1, 15, 17, 19, 30, 48, 52, 53, 79, 80, 416, 598
- Thrust coefficient 18, 31, 89
- Thrust law 13
- Thrust measurement 97, 98

- Thrust modulation 592, 593, 594, 597
- Thrust vector control 8
- Time-temperature equivalence 246-249
- TNT equivalence 308, 309
- Total impulse 20, 48, 55, 75, 96, 550
- Toxicity 586
- Transverse instabilities 174, 185, 401, 513
- Turbojet 594, 601
- Turboramjet 595, 601
- Unsteady combustion 140, 141, 164, 175
- Value analysis 361, 362
- Velocity coupling 175, 178, 183
- Viscoelasticity 235, 251, 336, 417, 418
- Viscosity 374, 380, 422, 431, 433, 442, 444, 451, 453, 495, 542, 568, 575, 578, 599
- Volume change 241, 388, 503
- Volumetric loading fraction 41, 55, 81, 549, 589
- Vulnerability 49, 345, 488, 593, 595, 598, 601
- XDT 311
- Zirconium 336, 403, 533-535, 537, 551, 586