

NV4108E-HS

Amcrest 4K 8CH Network Video Recorder

Technical Specifications

Model	NV4108E-HS
System	
Main Processor	Quad-core embedded processor
Operating System	Embedded LINUX
Audio/Video	
IP Camera Input	8 Channels
Two-way Talk	1 Channel Input, 1 Channel Output, RCA
Display	
Interface	1 HDMI, 1 VGA
Resolution	3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768
Decoding Capacity	2ch@8MP, 8ch @1080p
Multi-screen Display	1/4/8
OSD	Camera title, Time, Camera lock, Motion detection, Recording.
Recording	
Compression	H.265/H.264
Resolution	8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P/etc.
Playback	8ch@8MP, 30fps
Record Rate	80Mbps
Bit Rate	16Kbps ~ 20Mbps Per Channel
Record Mode	Manual, Schedule (Regular (Continuous), MD, Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec. Post record: 10~300 sec.
Video Detection and Alarm	
Trigger Events	Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), and Tampering

Playback and Backup	
Playback	1/4/8
Search Mode	Time /Date, MD, and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network
Network	
Interface	1 RJ-45 port (10/100Mbps)
Ethernet Port	1 Independent 100Mbps Ethernet Port
PoE	8 ports (IEEE802.3at/af) (4Mbps is recommended per channel)
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, IP Search
Max. User Access	128 users
Management Software	Amcrest View Pro app for IOS and Android, Amcrest Surveillance Pro (Recommended), Blue Iris Professional (Third Party), Web Browser (Pale Moon, Sea Monkey, Firefox 49.0.2, Internet Explorer, Chrome with Amcrest Extension, Safari 11).
Storage	
Internal HDD	1 SATA III Port, up to 6TB capacity for each HDD
HDD Mode	Single
Auxiliary Interface	
USB	2 ports (1 Rear USB2.0, 1 Front USB2.0)
Electrical	
Power Supply	DC48V, 2.0A
Power Consumption	NVR: <8.3W (Without HDD), PoE: Max 25.5w, single port, 80w total
Environmental	
Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH
Construction	
Dimensions(W×D×H)	Compact 1U, 260mm×224.9mm×47.6mm (10.2" x 8.9" x 1.9")
Net Weight	0.8kg (1.76 lbs.) (without HDD)
Gross Weight	1.6kg (3.53 lbs.) (without HDD)
Certifications	
CE	EN55032, EN55024, EN50130-4, EN60950-1

FCC	Part 15 Subpart B, ANSI C63.4-2014
UL	UL60950-1

Dimensions:

