



## KEY FEATURES

- Intel® Elkhart Lake SoC Processors
- 2 x 260-pin SO-DIMM up to 32GB DDR4 3200 MHz
- 4 x USB 3.2 Gen2, 1 x USB 2.0, 1 x M.2 Key M, 1 x M.2 Key E, 1 x SATA3
- 2 x Realtek 1 Gigabit LAN
- Supports Dual display, 1 x HDMI 2.0b, 1 x DP 1.2
- TPM 2.0 onboard IC
- 19V/65W Power Adapter
- 110.0 x 117.5 x 47.85mm, Fanned Barebone

## SPECIFICATIONS

### Processor System

CPU	Intel® Elkhart Lake SoC Processors
Chipset	NUC BOX-J6412 (J6412, QC, Max Speed up to 2.6GHz, 10W)
BIOS	SoC AMI SPI 256 Mbit

### Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	32GB (16 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

### Graphics

Controller	Intel® Gen 11 Graphics
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.2, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Dual-Display

### Expansion Slot

M.2/WLAN	1 x 802.11ac (433 Mbps) + BT 4.2 (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless)
----------	---

### Audio

Interface	Realtek ALC233, High Definition Audio.
-----------	--

### Ethernet

Controller/ Speed	Realtek RTL8111G-CG/RTL8111H-CG with 10/100/1000 Mbps
Connector	2 x RJ-45

### Internal Connector

TPM	Infineon SLB9670VQ2.0
-----	-----------------------

### Storage

M.2	1 x M.2 (KEY M, 2242/2260/2280) with PCIe x1 and SATA3 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

### Front I/O

USB	1 x USB 3.2 Gen2 (Type-A) 2 x USB 3.2 Gen2 (Type-C)
Audio	1 (headphone & microphone jack)

### Rear I/O

HDMI	1 x HDMI 2.0b
DisplayPort	1 x DP1.2
Ethernet	2 x 1 Gigabit LAN
USB	1 x USB 2.0 1 x USB 3.2 Gen2 (Type-A)
DC Jack	1

### Watchdog Timer

Output Interval	From Super I/O to drag RESETCON# 256 Segments, 0, 1, 2, ...255sec
-----------------	--

### Power Requirements

Input PWR Power On	1 x 19V/65W Power Adapter AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready
--------------------	--

### Environment

Operating Temp	0°C ~ 40°C
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

### Mechanical

Construction	Plastic
Mounting	VESA mounting
Dimensions (W x D x H)	110.0 x 117.5 x 47.85mm
Weight	Net Weight: 1.0kg

### Others

OS Support	Windows 10
Certifications	CE, FCC Class A
Packing List	1 x 19V/65W Power Adapter 1 x Screw Package 1 x VESA mounting bracket