

AERODROME
CHART - ICAO

ARP 191734.00N 0812127.97W

AD ELEVATION 9.5FT

OWEN ROBERTS INT'L- MWCR
Grand Cayman, Cayman Islands

GUND (Geoid Undulation) = -48FT The height of the Geoid (MSL) above the Reference Ellipsoid (WGS84) at the stated position	
BEARINGS ARE MAGNETIC ELEVATIONS AND HEIGHTS ARE IN FEET	
ELEVATIONS IN FEET AMSL	192
HEIGHTS IN FEET ABOVE AD	(68)

RUNWAY/TAXIWAY/APRON PHYSICAL CHARACTERISTICS		
APRON/RWY	SURFACE	BEARING STRENGTH
RWY 08/26	Asphalt Grooved	84/F/C/X/T
MAIN APRON	Asphalt and Concrete	Stands 1-8, 43/F/B/W/T
MAIN APRON	Asphalt and Concrete	Stands 9-14, 67/R/B/W/T
TAXIWAY A	Asphalt	111/F/D/X/T
TAXIWAY B	Asphalt	111/F/D/X/T
TAXIWAY C	Asphalt	85/F/A/W/T
TAXIWAY D	Asphalt	78/F/A/W/T
TAXIWAY E	Asphalt	30/F/A/W/T
TAXIWAY F	Asphalt	35/F/A/W/T
TAXIWAY G	Asphalt	111/F/D/X/T
TAXIWAY H	Asphalt	South of stands 1-8, 30/F/A/W/T
TAXIWAY H	Asphalt	South of stands 9-14, 67/R/B/W/T

DECLARED DISTANCES (metres)					
RWY	TORA	TODA	ASDA	LDA	THR Displacement
08	2275	2549	2275	2010	264.6
26	2134	2284	2134	2010	123.5

- NOTES
1. Aircraft shall not make final turn over George Town for landing Rwy 08.
 2. Flights below 1500FT prohibited except final descent for landing.
 3. The Threshold/ RWY end lights are raised 1FT above RWY surface.

