



Material :

Insulator : 30% Glass Fiber PBT, UL 94V-0
Contact : Phosphor Bronze, Gold flash plating

Specification :

Current : 3 Amp
Insulation Resistance : 5,000 Mohm min. at DC 500V
Contact resistance : 20 mOhm max. at DC 100mA
Dielectric Voltage : AC 500V for 1 minute
Operation temperature : - 40°C ~ + 105°C

Dimensions :

P/N	Poles	Dim. A	Dim. E
C-02762	1x5	10.16	13.20
C-03784	1x6	12.70	15.74
C-04285	1x7	15.24	18.28
C-03785	1x8	17.78	20.82
C-00653	1x14	33.02	36.06
C-03077	1x20	48.26	51.30

*** Poles available 1x3 ~ 1x40 pins**

E				Drawn	General Tolerance			Akizuki Denshi Tsusho Co., Ltd.		
D					.0	.00	.000			
C				Checked	± 0.20	±0.15	±0.05	Title : 2.54mm Female Header, Single row, Straight Dip type Insulator 8.5mm, Contacts 3.0mm (PCB Dip)		
B					Unit : mm					
A				Appraisal	Scale :		Part No.		Ref. Demensions table	File No. : UIC-FH-1X00SG
Rev.	Date	File	BY		Sheet : 1 / 1					