



Japan National Railways B20

During the later part of World War II, shunting locomotives were desperately needed in Japan. Owing to the wartime circumstances, authorities from different railway companies needed to form a special committee in order to develop and manufacture locomotives, such as B20. Its design was simple and low cost - in fact it was the only saturated, (non-superheated), steam locomotive on the JNR roster. Production began in 1944 and lasted until 1947. Tateyama and JNR's Kouriyama Works built fifteen locomotives. Some of continued in operation as late as 1972. A B20 is currently on display in the Umekoji Steam Locomotive Museum in Kyoto.



SPECIFICATIONS

Scale / Gauge: 1/24 G Gauge (45 mm)

Weight: 2.8 kg

Dimensions: Length O.C. 302 mm

Width: 106 mm

Height: 148 mm

Wheel Arrangement: 0-4-0 Four Wheeler (B)

Driving Wheels: Dia 35 mm

Engine Cylinders: 2 Cylinders, Bore 12 mm x Stroke 20 mm

Valve Gear: Walschaert, Valve Travel 5.0 mm. Cut-Off 84%

Boiler Type: Center Flue, Pressure 2 kg / cm² at normal working

Water Capacity: 120 cc at 80% full

Fittings: 2 x Safety Valves, Pressure Gauge, Water Gauge, Regulator Valve, Check Valve Filler Plug

Lubricator: Roscoe Displacement Type Located in the right side tank

Gas Tank Capacity: 31 cc Butane Gas Fuel

Minimum Radius: 0.55 m

Specifications subject to change without notice.



